

Model	Capacity		Element Options		Hours to Heat (12° - 85°)	Width x Depth x Height (")	Width x Depth x Height (mm)	Outlets
	Gallons	Litres	1-Phase	3-Phase				
WH30	30	135	3 KW		4.1	25 x 25 x 31	625 x 625 x 777	All 1 1/2"
WH40	40	180	3 / 4 KW		5.5 / 4.0	25 x 25 x 37	625 x 625 x 930	
WH50	50	225	4.8 KW	6 KW	4.2 / 3.4	25 x 25 x 43	625 x 625 x 1081	
WH60	60	270	4.8 / 6 KW	6 KW	5.2 / 4.1	25 x 25 x 49	625 x 625 x 1235	
WH70	70	315	6 KW	6 KW	4.8	27 x 27 x 45	690 x 690 x 1145	
WH80	80	360	6 KW	6 KW	5.5	27 x 27 x 49	690 x 690 x 1245	
WH100	100	450	6 KW	6 / 9 KW	7.0 / 4.5	33 x 33 x 46	835 x 835 x 1165	
WH120	120	540		9 KW	5.7	33 x 33 x 51	835 x 835 x 1285	
WH150	150	675		2 x 6 KW	5.1	39 x 39 x 50	990 x 990 x 1270	2" Outlet, 1 1/2" Drain and Overflow
WH200	200	900		2 x 6 KW	7	48 x 41 x 50	1210 x 1030 x 1270	
WH240	240	1080		3 x 6 KW	5.5	57 x 41 x 50	1440 x 1030 x 1270	
WH300	300	1350		3 x 9 KW	4.7	68 x 41 x 50	1735 x 1030 x 1270	